
PRODUCT-DETAILS

XF20/30M

XTRA FLEX 20MM REELED



General Information

Extended Product Type	XF20/30M
Product ID	7TCA296060R0112
EAN	5020963000270
Catalog Description	XTRA FLEX 20MM REELED
Long Description	Standard Weight Conduit, Nominal Conduit Size 20mm, Outside Diameter 20.5mm, Inside Diameter 16.0mm, Static Bend Radius 35mm, Reel Length 30 Meters, PVCu Spiral with Plasticised PVC Covering, Black

Ordering

EAN	5020963000270
Customs Tariff Number	3926909990

Dimensions

Product Net Weight	28.29 lb 12.83 kg
--------------------	----------------------

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	37 in 940 mm

Package Level 2 Height	17 in 432 mm
Package Level 2 Depth / Length	17 in 432 mm

Additional Information

Application	Indoors / Outdoors, Torsional Equipment
Brand / Label	Adaptaflex
Color	Black
Flexibility	Very High
Inside Diameter	16.0 mm
Material	PVCu Spiral with Plasticised Covering
Nominal Size	20 mm
Number of Batteries	0
Outside Diameter	20.5 mm
Product Name	ADAPTAFLEX
Product Type	Standard Weight Conduit
Radius	35 mm
Special Functions	High UV Protection
UPC	786210253343

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	XF20/30M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	XF20/30M

Classifications

ETIM 6	EC001175 - Corrugated plastic hose
ETIM 7	EC001175 - Corrugated plastic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

